

according to WHS Regulations

Printing date 22.02.2019 Version number 6 Revision: 22.02.2019

1 Identification

- Product identifier

- Trade name: Super pistol spray, silicone-free

- Relevant identified uses of the substance or

mixture and uses advised against

Identified use: intended for professional use only!

Application of the substance / the mixture Coating
 Details of the supplier of the safety data sheet

- Manufacturer/Supplier:

Alexander BINZEL

Schweißtechnik GmbH & Co.KG Postfach 10 01 53 /

D-35331 Giessen Tel.: +49 (0) 6408 / 59-0 Fax: +49 (0) 6408 / 59-191

Mail: technischedokumentation@binzel-abicor.com

- Further information obtainable from: Technische Dokumentation

- 1.4 Emergency telephone number: Giftinformationszentrum der Länder Rheinland-Pfalz und Hessen

Langenbeckstraße 1; Gebäude 601; 55131 Mainz

Tel. Nr.: +49 (0)6131 / 19 24 0

Universitätsmedizin der Johannes Gutenberg-Universität Mainz

Sales company: Binzel Pty. Ltd., 42 Hinkler Rd, Mordialloc, Victoria, 3195,

Australia

Responsible Person:

Phone:
+61 (0)39580 6500
e-Mail:
Stuart@binzel.com.au

Information in case of Emergency: Poison Information Center Tel.: 131 126

2 Hazard(s) Identification

- Classification of the substance or mixture

Aerosol 1 H222 Extremely flammable aerosol.

- Label elements

GHS label elements
 Hazard pictograms

The product is classified and labelled according to the Globally Harmonised System (GHS).

(A)

- Signal word Danger

- Hazard statements H222 Extremely flammable aerosol.

- Precautionary statements P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking.

P211 Do not spray on an open flame or other ignition source.
P251 Pressurized container: Do not pierce or burn, even after use.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses,

if present and easy to do. Continue rinsing.

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.

P501 Dispose of contents/container in accordance with local/regional/national/international

regulations.

- Other hazards

- Results of PBT and vPvB assessment

- PBT: Not applicable.
- vPvB: Not applicable.

3 Composition and Information on Ingredients

Chemical characterisation: Mixtures

- **Description:** Mixture: consisting of the following components

- Dangerous components:

106-97-8 | butane | 50-100%

74-98-6 | propane | 12.5-25%

75-28-5 | isobutane | 2.5-10%

- Additional information: For the wording of the listed hazard phrases refer to section 16.

EN-AU

(Contd. on page 2)



according to WHS Regulations

Printing date 22.02.2019 Version number 6 Revision: 22.02.2019

Trade name: Super pistol spray, silicone-free

(Contd. of page 1)

4 First Aid Measures

- Description of first aid measures

- General information: Immediately remove any clothing soiled by the product.

Symptoms of poisoning may even occur after several hours; therefore medical observation for at least 48

hours after the accident.

Do not leave affected persons unattended.

Personal protection for the First Aider.

Take affected persons out of danger area and lay down. In case of unconsciousness place patient stably in side position for transportation.

Supply fresh air; consult doctor in case of complaints.

Immediately wash with water and soap and rinse thoroughly.

Seek medical treatment in case of complaints. Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

Protect unharmed eve.

- After swallowing: If symptoms persist consult doctor.

- Information for doctor:

- After inhalation:

- After skin contact:

- After eye contact:

- Most important symptoms and effects, both

acute and delayed Indication of any immediate medical

attention and special treatment needed

No further relevant information available. No further relevant information available.

5 Fire Fighting Measures

- Extinguishing media

- Suitable extinguishing agents: CO2, powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

Use fire extinguishing methods suitable to surrounding conditions.

- For safety reasons unsuitable extinguishing

Water with full jet

 Special hazards arising from the substance or mixture

Nitrogen oxides (NOx)

Carbon monoxide (CO)

Formation of toxic gases is possible during heating or in case of fire.

- Advice for firefighters

- Protective equipment:

Do not inhale explosion gases or combustion gases.

- Additional information Collect contaminated fire fighting water separately. It must not enter the sewage system.

Dispose of fire debris and contaminated fire fighting water in accordance with official regulations.

6 Accidental Release Measures

Personal precautions, protective equipment

and emergency procedures

Wear protective equipment. Keep unprotected persons away.

Avoid contact with skin and eyes Ensure adequate ventilation Keep away from ignition sources.

- Environmental precautions:

Inform respective authorities in case of seepage into water course or sewage system.

Prevent from spreading (e.g. by damming-in or oil barriers). Do not allow to enter sewers/ surface or ground water.

- Methods and material for containment and

cleaning up:

Dispose contaminated material as waste according to item 13.

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust).

Do not flush with water or aqueous cleansing agents

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

7 Handling and Storage

- Reference to other sections

- Handling:

- Precautions for safe handling Store in cool, dry place in tightly closed receptacles. Ensure good ventilation/exhaustion at the workplace.

- Information about fire - and explosion

protection:

Keep ignition sources away - Do not smoke. Protect against electrostatic charges.

- Conditions for safe storage, including any incompatibilities
- Requirements to be met by storerooms and

receptacles:

Store only in the original receptacle.

Observe official regulations on storing packagings with pressurised containers.

(Contd. on page 3)

(Contd. of page 2)



Safety Data Sheet

according to WHS Regulations

Printing date 22.02.2019 Revision: 22.02.2019 Version number 6

Trade name: Super pistol spray, silicone-free

- Information about storage in one common

storage facility:

Store away from foodstuffs.

Further information about storage

conditions:

Protect from frost. Store in dry conditions. Keep container tightly sealed. Protect from heat and direct sunlight.

Recommended storage temperature: 5-30 °C

Storage class:

- Specific end use(s) No further relevant information available.

2 B

8 Exposure controls and personal protection

- Additional information about design of

technical facilities: No further data: see item 7.

Control parameters

- Ingredients with limit values that require monitoring at the workplace:

106-97-8 butane

NES | Long-term value: 1900 mg/m³, 800 ppm WES Long-term value: 1900 mg/m³, 800 ppm

74-98-6 propane

NES | Asphyxiant WES Asphyxiant

 Additional information: The lists valid during the making were used as basis.

Exposure controls

- Personal protective equipment:

- General protective and hygienic measures: The usual precautionary measures are to be adhered to when handling chemicals.

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

When used properly and under normal conditions, breathing protection is not required. - Respiratory protection:

Use suitable respiratory protective device in case of insufficient ventilation.

Filter A/P2

Respiratory protection - Gas filters and combination filters according to EN 141

- Protection of hands:



Protective gloves

Check protective gloves prior to each use for their proper condition. Only use chemical-protective gloves with CE-labelling of category III.

The glove material has to be impermeable and resistant to the product/ the substance/ the

preparation.

Selection of the glove material on consideration of the penetration times, rates of diffusion

and the degradation

After use of gloves apply skin-cleaning agents and skin cosmetics.

- Material of gloves Recommended materials:

Butyl rubber, BR

Recommended thickness of the material: ≥ 0.5 mm

Penetration time (min.): < 480

The selection of the suitable gloves does not only depend on the material, but also on further marks of

quality and varies from manufacturer to manufacturer.

- Penetration time of glove material The determined penetration times according to EN 374 part III are not performed under practical

conditions. Therefore a maximum wearing time, which corresponds to 50% of the penetration time, is

recommended. - As protection from splashes gloves made of

the following materials are suitable:

Nitrile rubber, NBR

Recommended thickness of the material: ≥ 0.1 mm

Penetration time (min.): < 10

- Eye protection:



Tightly sealed goggles

Protective goggles and facial protection - Classification according to EN 166

- Body protection: protective clothing (EN 13034)

EN-AU

(Contd. on page 4)



Printing date 22.02.2019

Safety Data Sheet

according to WHS Regulations Version number 6

Trade name: Super pistol spray, silicone-free

(Contd. of page 3)

Revision: 22.02.2019

9 Physical and Chemical Properties	
- Information on basic physical and chemica - General Information	ıl properties
- Appearance:	
Form:	Aerosol
Colour:	Opaque
- Odour:	Odourless
- Odour threshold:	Not determined.
- pH-value:	Not determined.
- Change in condition	
Melting point/freezing point:	Undetermined.
Initial boiling point and boiling range:	Not applicable, as aerosol.*
- Flash point:	Not applicable, as aerosol.*
- Flammability (solid, gas):	Not applicable.
- Ignition temperature:	Not determined.
- Decomposition temperature:	Not determined.
- Auto-ignition temperature:	Product is not selfigniting.
- Explosive properties:	Not determined.
- Explosion limits:	
Lower:	1.5 Vol %
Upper:	10.9 Vol %
- Density at 20 °C:	0.59 g/cm³
- Relative density	Not determined.
- Vapour density - Evaporation rate	Not determined.
· · · · · · · · · · · · · · · · · · ·	Not applicable.
- Solubility in / Miscibility with water:	Not miscible or difficult to mix.
- Partition coefficient: n-octanol/water:	Not determined.
- Viscosity:	
Dynamic:	Not determined.
Kinematic: - Other information	Not determined. No further relevant information available.
- Other information	NO IUI II EI PEEVATI III III III AVAIIADIE.

10 Stability and Reactivity

- Reactivity No further relevant information available.

- Chemical stability

- Thermal decomposition / conditions to be

avoided:

No decomposition if used according to specifications.

- Possibility of hazardous reactions

No dangerous reactions known.

- Conditions to avoid

No further relevant information available. - Incompatible materials: No further relevant information available. - Hazardous decomposition products: No dangerous decomposition products known.

11 Toxicological Information

- Information on toxicological effects
- Acute toxicity
- Primary irritant effect:
- Skin corrosion/irritation Based on available data, the classification criteria are not met.

12 Ecological Information

- Toxicity
- Aquatic toxicity:

106-97-8 butane

EC50 7.71 mg/l (ALGAE) (96h)

LC 50 27.98 mg/l (fish) (96h)

74-98-6 propane

EC50 7.71 mg/l (ALGAE) (96h)

(Contd. on page 5)



according to WHS Regulations

Printing date 22.02.2019 Revision: 22.02.2019 Version number 6

Trade name: Super pistol spray, silicone-free

(Contd. of page 4) LC50 | 27.98 mg/l (fish) (96h) 75-28-5 isobutane LC50 27.98 mg/l (fish) (96h) EC50 7.71 mg/l (ALGAE) (96h) No further relevant information available.

- Persistence and degradability - Behaviour in environmental systems:

- Bioaccumulative potential No further relevant information available. No further relevant information available. - Mobility in soil

- Additional ecological information:

- General notes: Do not allow undiluted product or large quantities of it to reach ground water, water course or sewage system.

Water hazard class 1 (German Regulation) (Self-assessment): slightly hazardous for water

- Results of PBT and vPvB assessment

- PBT: Not applicable. - vPvB: Not applicable.

No further relevant information available. - Other adverse effects

13 Disposal considerations

- Waste treatment methods

- Recommendation Must not be disposed together with household garbage. Do not allow product to reach sewage system.

Disposal according to official regulations

- Uncleaned packaging:

- Recommendation: Disposal must be made according to official regulations.

14 Transport information

- UN-Number - ADG, IMDG, IATA UN1950

- UN proper shipping name

1950 AEROSOLS - ADG - IMDG **AEROSOLS** AEROSOLS, flammable - IATA

- Transport hazard class(es)

- ADG



- Class 2 5F Gases.

Label

- IMDG, IATA



- Class 2.1 - Label 2.1

- Packing group

- ADG, IMDG, IATA Void

- Environmental hazards:

- Marine pollutant: No

- Special precautions for user Warning: Gases.

- Danger code (Kemler):

- EMS Number: F-D,S-U

- Stowage Code SW1 Protected from sources of heat.

SW22 For AEROSOLS with a maximum capacity of 1 litre: Category A. For

AEROSOLS with a capacity above 1 litre: Category B. For WASTE

AEROSOLS: Category C, Clear of living quarters.

(Contd. on page 6)

FN-AU



according to WHS Regulations

Printing date 22.02.2019 Version number 6 Revision: 22.02.2019

Trade name: Super pistol spray, silicone-free

	(Contd. of page 5)	
- Segregation Code	SG69 For AEROSOLS with a maximum capacity of 1 litre: Segregation as for class 9. Stow "separated from" class 1 except for division 1.4. For AEROSOLS with a capacity above 1 litre: Segregation as for the appropriate subdivision of class 2. For WASTE AEROSOLS: Segregation as for the appropriate subdivision of class 2.	
- Transport in bulk according to Annex II of Marpol and the IBC Code Not applicable.		
- Transport/Additional information:		
- ADG		
- Limited quantities (LQ)	1L	
- Excepted quantities (EQ)	Code: E0	
	Not permitted as Excepted Quantity	
- Transport category	2	
- Tunnel restriction code	D	
- IMDG		
- Limited quantities (LQ)	1L	
- Excepted quantities (EQ)	Code: E0	
	Not permitted as Excepted Quantity	
- UN "Model Regulation":	UN 1950 AEROSOLS, 2.1	

15 Regulatory information

- Safety, health and environmental regulations/legislation specific for the substance or mixture

- Australia	n Inventory of Chemical Substances
106-97-8	butane
74-98-6	propane
75-28-5	isobutane
04	for the Helfour Och addless of Medicines and Delegan

- Standard for the Uniform Scheduling of Medicines and Poisons

None of the ingredients is listed.

- Directive 2012/18/EU

- Named dangerous substances - ANNEX I

 Seveso category - Qualifying quantity (tonnes) for the None of the ingredients is listed. P3a FLAMMABLE AEROSOLS

application of lower-tier requirements

- Qualifying quantity (tonnes) for the application of upper-tier requirements 150 t 500 t

- National regulations:

- Information about limitation of use:

Employment restrictions concerning juveniles must be observed.

Employment restrictions concerning pregnant and lactating women must be observed. Employment restrictions concerning women of child-bearing age must be observed.

- Chemical safety assessment: A Chemical Safety Assessment has not been carried out.

16 Other information

This information is based on our present knowledge. However, this shall not constitute a guarantee for any specific product features and shall not establish a legally valid contractual relationship.

- Department issuing SDS: **Technical Documentation** - Contact: **Technical Documentation**

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International - Abbreviations and acronyms:

Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods

IATA: International Air Transport Association

EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service (division of the American Chemical Society) PBT: Persistent, Bioaccumulative and Toxic

vPvB: very Persistent and very Bioaccumulative Aerosol 1: Aerosols – Category 1

- Sources Internet:

- www.echa.europa.eu

www.baua.de

IFA: Institute für Occupational Safety and Health of the German Social Accident Insurance:

- www.dguv.de/ifa/gestis/gestis-stoffdatenbank/index.jsp

- www.dguv.de/ifa/gestis/gestis-dnel-liste

- * Data compared to the previous version altered.

EN-AU